





## Technical Pages

To facilitate retrieval, HOMA Pumps are supplied with either stainless steel lift handles or twin eye bolts for attaching shackles & chain. GRP & TP pumps, and D & T motor pumps are supplied with a short 304ss lift handle with tall 304ss or 316ss handle as an option. ET motors are supplied with a tall 304ss lift handle. P, F, G & H motor pumps are supplied with cast iron eye bolts with a tall 304ss or 316ss lift handle as an option. Refer to the chart below for more information

	Standard		Optional					
								
Motor Frame	A	B	Flat Stock	A	B	Round Stock	A	B
GRP10-50*	3 1/2"	4 1/2"	8734014	5"	4 1/2"	N/A		
D & TP Series	2"	4 1/2"	8734106	7 1/4"	4 1/2"	N/A		
T	4 1/2"	3 1/2"	8734128	7 1/4"	7"	8734102	9"	7 1/2"
ET	6"	7 1/4"	N/A					
								
Motor Frame	Eyebolt Dimensions (C15E steel) **		Flat Stock	A	B	Round Stock	A	B
P	M12 x 1.75 x 20mm 1 1/4" I.D.		8734110	12"	6"	8734111	12"	10"
F	M20 x 2.5 x 25mm 1 1/2" I.D.		8734112	12"	7 1/2"	8734113	11"	7"
G	M24 x 3 x 30mm 1 3/4" I.D.		8734114	7"	8 1/2"	8734274	12"	8 1/4"
H	M24 x 3 x 30mm 1 3/4" I.D.		8734284	12"	11 3/4"	8734284	12"	11 3/4"
R & S	Consult Factory							

\* For use with 8604019 Autocouplings

\*\* Eyebolts are installed from factory with Loctite. Use a torch to heat housing to remove eyebolt.